

| ESTIMATION DPR |        |                 |          |              |                   |                           |           |
|----------------|--------|-----------------|----------|--------------|-------------------|---------------------------|-----------|
| <b>State</b>   | Odisha | <b>District</b> | Rayagada | <b>Block</b> | Bissamcuttac<br>k | <b>Gram<br/>Panchayat</b> | Kutraguda |

|                         |  |
|-------------------------|--|
| <b>Work Code</b>        | OD/370/3547/121121/424981/00061746 (IMPROVEMENT OF AWC CENTRE AT LOHARAGUDI) |
| <b>Project Category</b> | Building   |

|                             |                                    |                              |  |
|-----------------------------|------------------------------------|------------------------------|--|
| <b>Financial Year</b>       | 2020-21                            | <b>Execution Level</b>       | PS   |
| <b>Executing Agency</b>     | Panchayat Samiti,<br>Bissamcuttack | <b>Proposal Date</b>         | -  |
| <b>Date of Commencement</b> | 06-12-2025                         | <b>Date of Completion</b>    | -  |
| <b>Scheme Name</b>          | SFC Devolution of Fund             | <b>Scheme Component Name</b> | 5TH SFC DEVOLUTION<br>GRANT TO PANCHAYAT<br>SAMITI |
| <b>Project Sub-Category</b> | AWC                                | <b>Project Type</b>          | New Work   |
| <b>Name of Executant</b>    | SAGAR GOUDA                        |                              |  |

#### Administrative Approval Details

|                     |                                       |
|---------------------|---------------------------------------|
| <b>Approval No.</b> | OD/370/3547/121121/424981/00061746/AS |
|---------------------|---------------------------------------|

#### Technical Sanction Details

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| <b>Technical Sanction No.</b>        | OD/370/3547/121121/424981/00061746/TS |
| <b>Fund Sanction No.</b>             |                                       |
| <b>Fund Sanction Amount (in Rs.)</b> | 200000                                |

#### ACTIVITY STATEMENT

| S/N | ACTIVITY TAKEN | UNIT | QUANTITY | UNIT PRICE (IN RS.) | TOTAL (IN RS.) |
|-----|----------------|------|----------|---------------------|----------------|
|-----|----------------|------|----------|---------------------|----------------|

|   |  |     |      |            |                |
|---|--|-----|------|------------|----------------|
| 1 | <p><b>Earth Work (AR0102aa) : Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift -</b><br/> Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift including rough dressing and breaking clods to maximum 5cm to 7cm and laying in layers not exceeding 0.3m in depth and as per the direction of the Engineer-in-charge</p> | Cum | 9.92 | 240.77592  | 6585.475927801 |
| 2 | <p><b>Earth Work (AR0115) : Filling foundation and plinth with sand well watered and rammed -</b> Filling foundation and plinth with sand well watered and rammed including cost, conveyance, royalty, taxes of all materials, labours and T &amp; P required for the work etc. complete and as per direction of Engineer-in charge.</p>   | Cum | 2.87 | 585.197232 | 6585.475927801 |

|   |   |     |      |               |                |
|---|---|-----|------|---------------|----------------|
| 3 | <p><b>Concrete (AR0303) :</b><br/> <b>Cement concrete (1:3:6) with 4 cm. Crusher Broken hard granite metal -</b> Cement concrete (1:3:6) with 4 cm. hard granite(Crusher Broken) metal including laying in layers not exceeding 300 mm in depth, ramming, compacting to proper thickness, watering and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&amp;P required for the work etc. complete and as per direction of Engineer-in charge.</p> | Cum | 6.05 | 5072.10660124 | 6585.475927801 |
|---|---|-----|------|---------------|----------------|

|   |   |     |       |                |                |
|---|---|-----|-------|----------------|----------------|
| 4 | <p><b>R.C.C. Work (AR0404Ab) :</b><br/> <b>Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br/> Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&amp;P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC Plinth band)</p> | Cum | 1.518 | 6377.623334995 | 6585.475927801 |
|---|---|-----|-------|----------------|----------------|

|   |   |     |     |                 |                |
|---|---|-----|-----|-----------------|----------------|
| 5 | <p><b>R.C.C. Work (AR0404Aa) : Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br/> Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&amp;P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC foundation, footing bases of column, mass concrete, pre-cast slabs etc.)</p> | Cum | 0.4 | 5620.0124653013 | 6585.475927801 |
|---|---|-----|-----|-----------------|----------------|

|   |   |     |         |                 |                |
|---|---|-----|---------|-----------------|----------------|
| 6 | <p><b>R.C.C. Work (AR0404Ac) :</b><br/> <b>Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br/> Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&amp;P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge. (RCC Beams, Column, Girder &amp; Bressmer etc)</p> | Cum | 0.27508 | 13675.765852621 | 6585.475927801 |
|---|---|-----|---------|-----------------|----------------|

|   |   |     |        |                |                |
|---|---|-----|--------|----------------|----------------|
| 7 | <p><b>Masonry Brick Work (AR0603bi) : Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure -</b><br/>         Brickwork with Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure having crushing strength not less than 75.00 Kg/cm<sup>2</sup> with dimensional tolerance <math>\pm 8</math> percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&amp;P required for the work, etc. complete and as per direction of Engineer-in-charge.</p> | Cum | 9.3702 | 4983.106127632 | 6585.475927801 |
|---|---|-----|--------|----------------|----------------|

|   |   |      |       |                |                |
|---|---|------|-------|----------------|----------------|
| 8 | <p><b>R.C.C. Work (AR0409) :</b><br/> <b>Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position -</b><br/> Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position including cost of binding wire 18 to 20 gauge with cost of steel rod and as per drawing, design, and direction of Engineer-in-charge.</p> | Qntl | 1.5   | 8940.2198886   | 6585.475927801 |
| 9 | <p><b>Plastering (AR1004) : 12mm thick cement plaster (1:6) over Brick work in inside -</b> 12mm thick cement plaster (1:6) over Brick work in inside including racking out joints finishing smooth with proper plumb and line curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T &amp; P required for the work etc. comp.and as per direction of Engineer-in-charge.</p>   | Sqm  | 40.74 | 166.4488307048 | 6585.475927801 |

|    |   |     |       |                 |                |
|----|---|-----|-------|-----------------|----------------|
| 10 | <p><b>Plastering (AR1014) : 16mm thick cement Plaster in CM (1:6) over brick work in inside. -</b><br/> 16mm thick cement Plaster in CM (1:6) over brick work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T &amp; P required for the work etc comp.and as per direction of Engineer-in-charge.</p> | Sqm | 40.74 | 240.018855108   | 6585.475927801 |
| 11 | <p><b>Painting (AR0918ca) : Finishing wall two coats with weather coat with one coat oilbound Primer -</b> Finishing wall surface two coats with weather coat with one coat oilbound Primer including all costs of labour, Paint, Primer, Brushes and putty required for the work etc. complete and as per direction of Engineer-in-charge.(Outside)</p>  | Sqm | 81.48 | 156.86604451751 | 6585.475927801 |

|    |   |      |          |                 |                |
|----|---|------|----------|-----------------|----------------|
| 12 | <p><b>Roofing (AR1132) : Supplying, feeting &amp; fixing of G.C.I. Sheet (0.30mm thick) in roof drilling hole in wind ties -</b><br/> Supplying, fitting &amp; fixing of G.C.I. Sheet (0.30mm thick) in roof drilling hole in wind ties including fixing of ridges valleys wind ties etc. including cost of fitting, Labour and material etc. complete as per direction of Engineer-in-Charge</p> | Sqm  | 9        | 521.52718361032 | 6585.475927801 |
| 13 | <p><b>Iron Work (AR1704) : Iron Doors and windows fixing -</b><br/> Supplying, fitting &amp; fixing of Mild steel and put up for frames &amp; shutters of Doors and windows fixing in position with cost, conveyance, taxes of all materials, labours and T &amp; P required for the work etc. as per direction of Engineer-in-charge.</p>  | Qntl | 2.588856 | 16258.658839087 | 6585.475927801 |

|   |  |      |      |                 |                |
|---|--|------|------|-----------------|----------------|
| 14  | <b>Flooring (AR0802ii) : 2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG Hand broken chips - 2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG Hand broken chips including punning incl. cost, conveyance &amp; royalty of materials as per direction of Engineer-in-charge.</b> | Sqm  | 9    | 346.2742706048  | 6585.475927801 |
| 15  | <b>Iron Work (AR1703) : Iron work wrought and put up in trusses and record racks - Iron work wrought and put up in trusses and record racks including all cost of labour, material, machinery and T &amp; P required for the work etc. as per direction of Engineer-in-Charge.</b>                       | Qntl | 0.48 | 13719.741516252 | 6585.475927801 |
| <b>Total Amount (in Rs.): 196376.41019972</b> |  |      |      |                 |                |

## LABOUR STATEMENT

| SI.No. | Activity Name | Qty/unit(B=Analysis Basic Qty/HeaderUnit) | Quantity(Measurement Qty) | Unit |
|--------|---------------|---|---------------------------|------|
|--------|---------------|---|---------------------------|------|

|   |  |        |          |     |
|---|--|--------|----------|-----|
| 1 | <p><b>Earth Work (AR0102aa) : Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift -</b></p> <p>Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift including rough dressing and breaking clods to maximum 5cm to 7cm and laying in layers not exceeding 0.3m in depth and as per the direction of the Engineer-in-charge</p> | -      | 9.92     | Cum |
| i | Un-Skilled   | 0.516  | 5.11872  | -   |
| 2 | <p><b>Earth Work (AR0115) : Filling foundation and plinth with sand well watered and rammed -</b></p> <p>Filling foundation and plinth with sand well watered and rammed including cost, conveyance, royalty, taxes of all materials, labours and T &amp; P required for the work etc. complete and as per direction of Engineer-in charge.</p>  | -      | 2.87     | Cum |
| i | Un-Skilled   | 0.1236 | 0.354732 | -   |

|    |  |      |        |     |
|----|--|------|--------|-----|
| 3  | <p><b>Concrete (AR0303) :<br/>Cement concrete (1:3:6) with 4 cm. Crusher Broken hard granite metal -</b><br/>Cement concrete (1:3:6) with 4 cm. hard granite(Crusher Broken) metal including laying in layers not exceeding 300 mm in depth, ramming, compacting to proper thickness, watering and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&amp;P required for the work etc. complete and as per direction of Engineer-in charge.</p>  | -    | 6.05   | Cum |
| i  | Skilled  | 0.18 | 1.089  | -   |
| ii | Un-Skilled   | 3.9  | 23.595 | -   |
| 4  | <p><b>R.C.C. Work (AR0404Ab) :<br/>Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br/>Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&amp;P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC Plinth band)</p> | -    | 1.518  | Cum |

|   |     |  |        |           |     |
|---|-----|--|--------|-----------|-----|
|   | i   | Un-Skilled   | 1.3333 | 2.0239494 | -   |
|   | ii  | Skilled  | 0.35   | 0.5313    | -   |
|   | iii | Semi-Skilled   | 0.3073 | 0.4664814 | -   |
| 5 |     | <b>R.C.C. Work (AR0404Aa) :</b><br><b>Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br>Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC foundation, footing bases of column, mass concrete, pre-cast slabs etc.) | -      | 0.4       | Cum |
|   | i   | Un-Skilled   | 1.3333 | 0.53332   | -   |
|   | ii  | Skilled  | 0.175  | 0.07      | -   |
|   | iii | Semi-Skilled   | 0.1323 | 0.05292   | -   |

|     |  |         |             |     |
|-----|--|---------|-------------|-----|
| 6   | <b>R.C.C. Work (AR0404Ac) :</b><br><b>Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br>Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge. (RCC Beams, Column, Girder & Bressmer etc) | -       | 0.27508     | Cum |
| i   | Un-Skilled   | 1.3333  | 0.366764164 | -   |
| ii  | Skilled  | 5.33875 | 1.46858335  | -   |
| iii | Semi-Skilled   | 5.29605 | 1.456837434 | -   |

|     |   |      |           |     |
|-----|---|------|-----------|-----|
| 7   | <b>Masonry Brick Work (AR0603bi) : Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure -</b><br>Brickwork with Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure having crushing strength not less than 75.00 Kg/cm <sup>2</sup> with dimensional tolerance ±8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&P required for the work, etc. complete and as per direction of Engineer-in-charge. | -    | 9.3702    | Cum |
| i   | Un-Skilled  | 2.96 | 27.735792 | -   |
| ii  | Skilled   | 1.05 | 9.83871   | -   |
| iii | Highly-Skilled  | 0.35 | 3.27957   | -   |

|     |   |       |        |      |
|-----|---|-------|--------|------|
| 8   | <p><b>R.C.C. Work (AR0409) : Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position -</b><br/> Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position including cost of binding wire 18 to 20 gauge with cost of steel rod and as per drawing, design, and direction of Engineer-in-charge.</p> | -     | 1.5    | Qntl |
| i   | Un-Skilled  | 0.8   | 1.2    | -    |
| ii  | Highly-Skilled  | 0.3   | 0.45   | -    |
| iii | Semi-Skilled  | 0.044 | 0.066  | -    |
| 9   | <p><b>Plastering (AR1004) : 12mm thick cement plaster (1:6) over Brick work in inside -</b> 12mm thick cement plaster (1:6) over Brick work in inside including racking out joints finishing smooth with proper plumb and line curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T &amp; P required for the work etc. comp.and as per direction of Engineer-in-charge.</p>   | -     | 40.74  | Sqm  |
| i   | Un-Skilled  | 0.12  | 4.8888 | -    |

|    |    |   |                  |                 |     |
|----|----|---|------------------|-----------------|-----|
|    | ii | Skilled   | 0.14             | 5.7036          | -   |
| 10 |    | <b>Plastering (AR1014) :<br/>16mm thick cement<br/>Plaster in CM (1:6)<br/>over brick work in<br/>inside.</b> - 16mm thick<br>cement Plaster in CM<br>(1:6) over brick work in<br>inside including racking<br>out joints finishing<br>smooth with proper<br>plumb and line, curing<br>for proper period with<br>cost conveyance,<br>royalty, taxes of all<br>materials, labour and T<br>& P required for the<br>work etc comp.and as<br>per direction of<br>Engineer-in-charge. | -                | 40.74           | Sqm |
|    | i  | Un-Skilled  | 0.24             | 9.7776          | -   |
|    | ii | Skilled   | 0.16             | 6.5184          | -   |
| 11 |    | <b>Painting (AR0918ca) :<br/>Finishing wall two<br/>coats with weather<br/>coat with one coat<br/>oilbound Primer -</b><br>Finishing wall surface<br>two coats with weather<br>coat with one coat<br>oilbound Primer<br>including all costs of<br>labour, Paint, Primer,<br>Brushes and putty<br>required for the work<br>etc. complete and as<br>per direction of<br>Engineer-in-<br>charge.(Outside)  | -                | 81.48           | Sqm |
|    | i  | Un-Skilled  | 0.11776344086022 | 9.5953651612903 | -   |
|    | ii | Highly-Skilled  | 0.10776344086022 | 8.7805651612903 | -   |

|     |   |                  |                 |      |
|-----|---|------------------|-----------------|------|
| 12  | <b>Roofing (AR1132) :<br/>Supplying, feeting &amp; fixing of G.C.I. Sheet (0.30mm thick) in roof drilling hole in wind ties</b> - Supplying, fitting & fixing of G.C.I. Sheet (0.30mm thick) in roof drilling hole in wind ties including fixing of ridges valleys wind ties etc. including cost of fitting, Labour and material etc. complete as per direction of Engineer-in-Charge | -                | 9               | Sqm  |
| i   | Un-Skilled  | 0.21505376344086 | 1.9354838709677 | -    |
| ii  | Highly-Skilled  | 0.16129032258065 | 1.4516129032258 | -    |
| 13  | <b>Iron Work (AR1704) :<br/>Iron Doors and windows fixing</b> - Supplying, fitting & fixing of Mild steel and put up for frames & shutters of Doors and windows fixing in position with cost, conveyance, taxes of all materials, labours and T & P required for the work etc. as per direction of Engineer-in-charge.  | -                | 2.588856        | Qntl |
| i   | Un-Skilled  | 6.3976377952756  | 16.562562992126 | -    |
| ii  | Semi-Skilled  | 1.9685039370079  | 5.0961732283465 | -    |
| iii | Skilled   | 3.9370078740157  | 10.192346456693 | -    |
| iv  | Highly-Skilled  | 3.4448818897638  | 8.9183031496063 | -    |

|     |  |                 |                  |      |
|-----|--|-----------------|------------------|------|
| 14  | <b>Flooring (AR0802ii) :<br/>2.5 cm thick A.S.<br/>flooring in C.C (1:2:4)<br/>with 12 mm size HG<br/>Hand broken chips -<br/>2.5 cm thick A.S.<br/>flooring in C.C (1:2:4)<br/>with 12 mm size HG<br/>Hand broken chips<br/>including punning incl.<br/>cost, conveyance &amp;<br/>royalty of materials as<br/>per direction of<br/>Engineer-in-charge.</b> | -               | 9                | Sqm  |
| i   | Un-Skilled   | 0.36            | 3.24             | -    |
| ii  | Highly-Skilled   | 0.13            | 1.17             | -    |
| 15  | <b>Iron Work (AR1703) :<br/>Iron work wrought<br/>and put up in trusses<br/>and record racks -<br/>Iron work wrought and<br/>put up in trusses and<br/>record racks including<br/>all cost of labour,<br/>material, machinery<br/>and T &amp; P required for<br/>the work etc. as per<br/>direction of Engineer-in-<br/>Charge.</b>                          | -               | 0.48             | Qntl |
| i   | Un-Skilled   | 4.9212598425197 | 2.3622047244094  | -    |
| ii  | Semi-Skilled   | 1.9685039370079 | 0.94488188976378 | -    |
| iii | Skilled  | 4.4291338582677 | 2.1259842519685  | -    |

| SI.No. | Labour Type | Qty Unit        | Rate | Amount          |
|--------|-------------|-----------------|------|-----------------|
| 0      | Un-Skilled  | 109.29029431279 | 462  | 50492.115972511 |
| 1      | Skilled     | 37.537924058661 | 562  | 21096.313320968 |

|   |                |                 |     |                               |
|---|----------------|-----------------|-----|-------------------------------|
| 2 | Semi-Skilled   | 8.0832939521102 | 512 | 4138.6465034804               |
| 3 | Highly-Skilled | 24.050051214122 | 612 | 14718.631343043               |
|   |                |                 |     | <b>Total: 90445.707140002</b> |

## MATERIAL STATEMENT

| SI.No. | Activity Name/Material  | Qty/unit (B=Analysis Basic Qty/Header Unit) | Quantity (Meaurement Qty) | Unit  |
|--------|---|---|---------------------------|-------|
| 1      | <b>Earth Work (AR0102aa) :.Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift -</b><br>Earth work in hard soil or gravelly soil foundation & plinth within 50m. Initial lead and 1.5m initial lift including rough dressing and breaking clods to maximum 5cm to 7cm and laying in layers not exceeding 0.3m in depth and as per the direction of the Engineer-in-charge | -   | <b>9.92</b>               | Cum   |
| 2      | <b>Earth Work (AR0115) :.Filling foundation and plinth with sand well watered and rammed -</b> Filling foundation and plinth with sand well watered and rammed including cost, conveyance, royalty, taxes of all materials, labours and T & P required for the work etc. complete and as per direction of Engineer-in charge.   | -   | <b>2.87</b>               | Cum   |
| i)     | <b>BRM029 : Sand for filling and road blinding</b>  | 1   | 2.87                      | 1 Cum |

|      |   |        |           |         |
|------|---|--------|-----------|---------|
| 3    | <p><b>Concrete (AR0303)</b><br/> <b>:.Cement concrete (1:3:6) with 4 cm. Crusher Broken hard granite metal -</b><br/> Cement concrete (1:3:6) with 4 cm. hard granite(Crusher Broken) metal including laying in layers not exceeding 300 mm in depth, ramming, compacting to proper thickness, watering and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&amp;P required for the work etc. complete and as per direction of Engineer-in charge.</p>  | -      | 6.05      | Cum     |
| i)   | <b>BRM340 : Cement</b>  | 2.29   | 13.8545   | 1 Qntl. |
| ii)  | <b>BRM028 : Screened and washed sharp sand for mortar</b>   | 0.48   | 2.904     | 1 Cum   |
| iii) | <b>BRM044 : Granite Stone broken metal 40mm. size (Crusher broken)</b>  | 0.96   | 5.808     | 1 Cum.  |
| 4    | <p><b>R.C.C. Work (AR0404Ab)</b><br/> <b>:.Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br/> Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&amp;P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC Plinth band)</p> | -      | 1.518     | Cum     |
| i)   | <b>BRM340 : Cement</b>  | 3.4733 | 5.2724694 | 1 Qntl. |

|      |  |         |           |         |
|------|--|---------|-----------|---------|
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.45    | 0.6831    | 1 Cum   |
| iii) | <b>BRM060</b> : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)   | 0.36    | 0.54648   | 1 Cum.  |
| iv)  | <b>BRM052</b> : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)   | 0.54    | 0.81972   | 1 Cum.  |
| v)   | <b>BRM104</b> : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)  | 0.01335 | 0.0202653 | 1Cum.   |
| vi)  | <b>BRM092</b> : Non-sal bullahs 75mm. mean dia of any length.  | 0.63    | 0.95634   | 1Mtr.   |
| 5    | <b>R.C.C. Work (AR0404Aa)</b><br>:.Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips - Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC foundation, footing bases of column, mass concrete, pre-cast slabs etc.) | -       | 0.4       | Cum     |
| i)   | <b>BRM340</b> : Cement   | 3.4733  | 1.38932   | 1 Qntl. |

|      |  |          |                |         |
|------|--|----------|----------------|---------|
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.45     | 0.18           | 1 Cum   |
| iii) | <b>BRM060</b> : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)   | 0.36     | 0.144          | 1 Cum.  |
| iv)  | <b>BRM052</b> : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)   | 0.54     | 0.216          | 1 Cum.  |
| v)   | <b>BRM104</b> : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)  | 0.004005 | 0.001602       | 1Cum.   |
| vi)  | <b>BRM092</b> : Non-sal bullahs 75mm. mean dia of any length.  | 0.189    | 0.0756         | 1Mtr.   |
| 6    | <b>R.C.C. Work (AR0404Ac)</b><br>:.Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips - Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge. (RCC Beams, Column, Girder & Bressmer etc) | -        | <b>0.27508</b> | Cum     |
| i)   | <b>BRM340</b> : Cement   | 3.4733   | 0.955435364    | 1 Qntl. |

|      |  |          |               |         |
|------|--|----------|---------------|---------|
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.45     | 0.123786      | 1 Cum   |
| iii) | <b>BRM060</b> : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)   | 0.36     | 0.0990288     | 1 Cum.  |
| iv)  | <b>BRM052</b> : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)   | 0.54     | 0.1485432     | 1 Cum.  |
| v)   | <b>BRM084</b> : Sal bullahs 75mm. to 120mm. mean dia up to 5.5m. long.   | 4.4196   | 1.215743568   | 1Mtr    |
| vi)  | <b>BRM104</b> : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)  | 0.041529 | 0.01142379732 | 1Cum.   |
| 7    | <b>Masonry Brick Work (AR0603bi) :Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure -</b><br>Brickwork with Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure having crushing strength not less than 75.00 Kg/cm <sup>2</sup> with dimensional tolerance ±8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&P required for the work, etc. complete and as per direction of Engineer-in-charge. | -        | <b>9.3702</b> | Cum     |
| i)   | <b>BRMMR0025</b> : SCAFFOLDING CHARGES FOR BRICK MASONRY WORK  | 1        | 9.3702        | 1 Cum   |
| ii)  | <b>BRM340</b> : Cement   | 0.672    | 6.2967744     | 1 Qntl. |

|      |  |        |          |          |
|------|--|--------|----------|----------|
| iii) | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.28   | 2.623656 | 1 Cum    |
| iv)  | <b>BRM005</b> : Fly ash bricks of 25 Cm. x 12 Cm. x 8 Cm. size having crushing strength not less than 75 Kg./Cm <sup>2</sup> with dimensional tolerance $\pm$ 2 %  | 350    | 3279.57  | 1000 Nos |
| 8    | <b>R.C.C. Work (AR0409) :.Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position -</b><br>Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position including cost of binding wire 18 to 20 gauge with cost of steel rod and as per drawing, design, and direction of Engineer-in-charge. | -      | 1.5      | Qntl     |
| i)   | <b>BRM162</b> : Binding Wire.  | 0.8    | 1.2      | 1 Kg.    |
| ii)  | <b>BRM341</b> : Steel  | 1.05   | 1.575    | 1 Qntl.  |
| 9    | <b>Plastering (AR1004) :.12mm thick cement plaster (1:6) over Brick work in inside -</b> 12mm thick cement plaster (1:6) over Brick work in inside including racking out joints finishing smooth with proper plumb and line curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc. comp.and as per direction of Engineer-in-charge.   | -      | 40.74    | Sqm      |
| i)   | <b>BRM340</b> : Cement   | 0.0358 | 1.458492 | 1 Qntl.  |
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.015  | 0.6111   | 1 Cum    |

|     |  |       |         |         |
|-----|--|-------|---------|---------|
| 10  | <b>Plastering (AR1014)</b><br>∴.16mm thick cement Plaster in CM (1:6) over brick work in inside. - 16mm thick cement Plaster in CM (1:6) over brick work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc comp.and as per direction of Engineer-in-charge. | -     | 40.74   | Sqm     |
| i)  | <b>BRM340</b> : Cement   | 0.043 | 1.75182 | 1 Qntl. |
| ii) | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.018 | 0.73332 | 1 Cum   |
| 11  | <b>Painting(AR0918ca)</b><br>∴.Finishing wall two coats with weather coat with one coat oilbound Primer - Finishing wall surface two coats with weather coat with one coat oilbound Primer including all costs of labour, Paint, Primer, Brushes and putty required for the work etc. complete and as per direction of Engineer-in-charge.(Outside)  | -     | 81.48   | Sqm     |
| i)  | <b>BRM255</b> : Weather Coat (I.S.I.)  | 0.125 | 10.185  | 1 Ltr   |
| ii) | <b>BRM252</b> : Wall cement primer (I.S.I.) Oil bound  | 0.084 | 6.84432 | 1 Ltr   |
| 12  | <b>Roofing (AR1132)</b><br>∴.Supplying, feeting & fixing of G.C.I. Sheet (0.30mm thick) in roof drilling hole in wind ties - Supplying, fitting & fixing of G.C.I. Sheet (0.30mm thick) in roof drilling hole in wind ties including fixing of ridges valleys wind ties etc. including cost of fitting, Labour and material etc. complete as per direction of Engineer-in-Charge   | -     | 9       | Sqm     |

|      |  |        |                 |         |
|------|--|--------|-----------------|---------|
| i)   | <b>BRM149 : G.C.I. Sheet</b><br>0.30mm thick   | 1      | 9               | 1 Sqm   |
| 13   | <b>Iron Work(AR1704)</b><br><b>:.Iron Doors and windows fixing -</b><br>Supplying, fitting & fixing of Mild steel and put up for frames & shutters of Doors and windows fixing in position with cost, conveyance, taxes of all materials, labours and T & P required for the work etc. as per direction of Engineer-in-charge. | -      | <b>2.588856</b> | Qntl    |
| i)   | <b>BRM341 : Steel</b>  | 1      | 2.588856        | 1 Qntl. |
| 14   | <b>Flooring (AR0802ii)</b><br><b>:.2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG Hand broken chips -</b><br>2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG Hand broken chips including punning incl. cost, conveyance & royalty of materials as per direction of Engineer-in-charge.              | -      | <b>9</b>        | Sqm     |
| i)   | <b>BRM340 : Cement</b>   | 0.0858 | 0.7722          | 1 Qntl. |
| ii)  | <b>BRM028 : Screened and washed sharp sand for mortar</b>  | 0.012  | 0.108           | 1 Cum   |
| iii) | <b>BRM057 : Granite Stone broken chips</b><br>12mm. size (Minimum 65% by Wt. Passing through 13.2mm sieve & retained on 9.50mm sieve but whole should pass through 19mm sieve)(Hand broken)  | 0.023  | 0.207           | 1 Cum.  |
| 15   | <b>Iron Work(AR1703)</b><br><b>:.Iron work wrought and put up in trusses and record racks -</b><br>Iron work wrought and put up in trusses and record racks including all cost of labour, material, machinery and T & P required for the work etc. as per direction of Engineer-in-Charge.                                     | -      | <b>0.48</b>     | Qntl    |
| i)   | <b>BRM341 : Steel</b>  | 1      | 0.48            | 1 Qntl. |

| Sl.No.                        | Material Name | Qty           | Unit     | Rate       | Amount          |
|-------------------------------|---------------|---------------|----------|------------|-----------------|
| 1                             | BRM029        | 2.87          | 1 Cum    | 413.05     | 1185.4535       |
| 2                             | BRM340        | 31.751011164  | 1 Qntl.  | 543.752    | 17264.675822447 |
| 3                             | BRM028        | 7.966962      | 1 Cum    | 417.99     | 3330.11044638   |
| 4                             | BRM044        | 5.808         | 1 Cum.   | 1291.11    | 7498.76688      |
| 5                             | BRM060        | 0.7895088     | 1 Cum.   | 1759.78    | 1389.361796064  |
| 6                             | BRM052        | 1.1842632     | 1 Cum.   | 1723.4     | 2040.95919888   |
| 7                             | BRM104        | 0.03329109732 | 1Cum.    | 58620.646  | 1951.5456309473 |
| 8                             | BRM092        | 1.03194       | 1Mtr.    | 276.666    | 285.50271204    |
| 9                             | BRM084        | 1.215743568   | 1Mtr     | 250.166    | 304.13770543229 |
| 10                            | BRMMR0025     | 9.3702        | 1 Cum    | 33         | 309.2166        |
| 11                            | BRM005        | 3279.57       | 1000 Nos | 6.1539     | 20182.145823    |
| 12                            | BRM162        | 1.2           | 1 Kg.    | 90.1       | 108.12          |
| 13                            | BRM341        | 4.643856      | 1 Qntl.  | 6626.072   | 30770.524213632 |
| 14                            | BRM255        | 10.185        | 1 Ltr    | 195.09732  | 1987.0662042    |
| 15                            | BRM252        | 6.84432       | 1 Ltr    | 125.80732  | 861.0655564224  |
| 16                            | BRM149        | 9             | 1 Sqm    | 318.299032 | 2864.691288     |
| 17                            | BRM057        | 0.207         | 1 Cum.   | 1391.11    | 287.95977       |
| <b>Total: 92621.303147445</b> |               |               |          |            |                 |

## ROYALTY STATEMENT

| Sl.No. | Activity Name/Material   | Qty/unit (B=Analysis Basic Qty/Header Unit) | Quantity (Meaurement Qty) | Unit |
|--------|--|---|---------------------------|------|
| 1      | <p><b>Earth Work (AR0102aa) :.Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift -</b></p> <p>Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift including rough dressing and breaking clods to maximum 5cm to 7cm and laying in layers not exceeding 0.3m in depth and as per the direction of the Engineer-in-charge</p> | -   | <b>9.92</b>               | Cum  |

|      |   |      |         |         |
|------|---|------|---------|---------|
| 2    | <b>Earth Work (AR0115)</b><br>:.Filling foundation and plinth with sand well watered and rammed - Filling foundation and plinth with sand well watered and rammed including cost, conveyance, royalty, taxes of all materials, labours and T & P required for the work etc. complete and as per direction of Engineer-in charge.  | -    | 2.87    | Cum     |
| i)   | <b>BRM029</b> : Sand for filling and road blinding  | 1    | 2.87    | 1 Cum   |
| 3    | <b>Concrete (AR0303)</b><br>:.Cement concrete (1:3:6) with 4 cm. Crusher Broken hard granite metal - Cement concrete (1:3:6) with 4 cm. hard granite(Crusher Broken) metal including laying in layers not exceeding 300 mm in depth, ramming, compacting to proper thickness, watering and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&P required for the work etc. complete and as per direction of Engineer-in charge. | -    | 6.05    | Cum     |
| i)   | <b>BRM340</b> : Cement  | 2.29 | 13.8545 | 1 Qntl. |
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar   | 0.48 | 2.904   | 1 Cum   |
| iii) | <b>BRM044</b> : Granite Stone broken metal 40mm. size (Crusher broken)  | 0.96 | 5.808   | 1 Cum.  |

|      |  |         |            |         |
|------|--|---------|------------|---------|
| 4    | <b>R.C.C. Work (AR0404Ab)</b><br><b>:.Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br>Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC Plinth band) | -       | 1.518      | Cum     |
| i)   | <b>BRM340</b> : Cement   | 3.4733  | 5.2724694  | 1 Qntl. |
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.45    | 0.6831     | 1 Cum   |
| iii) | <b>BRM060</b> : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)   | 0.36    | 0.54648    | 1 Cum.  |
| iv)  | <b>BRM052</b> : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)   | 0.54    | 0.81972    | 1 Cum.  |
| v)   | <b>BRM104</b> : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)  | 0.01335 | 0.0202653  | 1Cum.   |
| vi)  | <b>BRM092</b> : Non-sal bullahs 75mm. mean dia of any length.  | 0.00307 | 0.00466026 | 1Mtr.   |

|      |   |          |           |         |
|------|---|----------|-----------|---------|
| 5    | <p><b>R.C.C. Work (AR0404Aa)</b><br/> <b>:.Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br/> Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&amp;P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC foundation, footing bases of column, mass concrete, pre-cast slabs etc.)</p> | -        | 0.4       | Cum     |
| i)   | <b>BRM340</b> : Cement  | 3.4733   | 1.38932   | 1 Qntl. |
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar   | 0.45     | 0.18      | 1 Cum   |
| iii) | <b>BRM060</b> : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)  | 0.36     | 0.144     | 1 Cum.  |
| iv)  | <b>BRM052</b> : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)  | 0.54     | 0.216     | 1 Cum.  |
| v)   | <b>BRM104</b> : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)   | 0.004005 | 0.001602  | 1Cum.   |
| vi)  | <b>BRM092</b> : Non-sal bullahs 75mm. mean dia of any length.   | 0.000921 | 0.0003684 | 1Mtr.   |

|      |  |          |                |         |
|------|--|----------|----------------|---------|
| 6    | <b>R.C.C. Work (AR0404Ac)</b><br><b>:.Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b><br>Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge. (RCC Beams, Column, Girder & Bressmer etc) | -        | <b>0.27508</b> | Cum     |
| i)   | <b>BRM340</b> : Cement   | 3.4733   | 0.955435364    | 1 Qntl. |
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.45     | 0.123786       | 1 Cum   |
| iii) | <b>BRM060</b> : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)   | 0.36     | 0.0990288      | 1 Cum.  |
| iv)  | <b>BRM052</b> : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)   | 0.54     | 0.1485432      | 1 Cum.  |
| v)   | <b>BRM084</b> : Sal bullahs 75mm. to 120mm. mean dia up to 5.5m. long.   | 0.045339 | 0.01247185212  | 1Mtr    |
| vi)  | <b>BRM104</b> : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)  | 0.041529 | 0.01142379732  | 1Cum.   |

|      |   |       |           |          |
|------|---|-------|-----------|----------|
| 7    | <p><b>Masonry Brick Work (AR0603bi) :.Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure -</b><br/> Brickwork with Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure having crushing strength not less than 75.00 Kg/cm<sup>2</sup> with dimensional tolerance ±8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&amp;P required for the work, etc. complete and as per direction of Engineer-in-charge.</p> | -     | 9.3702    | Cum      |
| i)   | <b>BRM340</b> : Cement  | 0.672 | 6.2967744 | 1 Qntl.  |
| ii)  | <b>BRM028</b> : Screened and washed sharp sand for mortar   | 0.28  | 2.623656  | 1 Cum    |
| iii) | <b>BRM005</b> : Fly ash bricks of 25 Cm. x 12 Cm. x 8 Cm. size having crushing strength not less than 75 Kg./Cm <sup>2</sup> with dimensional tolerance ± 2 %   | 350   | 3279.57   | 1000 Nos |
| 8    | <p><b>R.C.C. Work (AR0409) :.Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position -</b><br/> Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position including cost of binding wire 18 to 20 gauge with cost of steel rod and as per drawing, design, and direction of Engineer-in-charge.</p>                                       | -     | 1.5       | Qntl     |
| i)   | <b>BRM341</b> : Steel   | 1.05  | 1.575     | 1 Qntl.  |

|     |  |        |          |         |
|-----|--|--------|----------|---------|
| 9   | <b>Plastering (AR1004)</b><br>:.12mm thick cement plaster (1:6) over Brick work in inside - 12mm thick cement plaster (1:6) over Brick work in inside including racking out joints finishing smooth with proper plumb and line curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc. comp.and as per direction of Engineer-in-charge.              | -      | 40.74    | Sqm     |
| i)  | <b>BRM340</b> : Cement   | 0.0358 | 1.458492 | 1 Qntl. |
| ii) | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.015  | 0.6111   | 1 Cum   |
| 10  | <b>Plastering (AR1014)</b><br>:.16mm thick cement Plaster in CM (1:6) over brick work in inside. - 16mm thick cement Plaster in CM (1:6) over brick work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc comp.and as per direction of Engineer-in-charge. | -      | 40.74    | Sqm     |
| i)  | <b>BRM340</b> : Cement   | 0.043  | 1.75182  | 1 Qntl. |
| ii) | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.018  | 0.73332  | 1 Cum   |
| 11  | <b>Painting(AR0918ca)</b><br>:.Finishing wall two coats with weather coat with one coat oilbound Primer - Finishing wall surface two coats with weather coat with one coat oilbound Primer including all costs of labour, Paint, Primer, Brushes and putty required for the work etc. complete and as per direction of Engineer-in-charge.(Outside)  | -      | 81.48    | Sqm     |

|     |  |        |          |         |
|-----|--|--------|----------|---------|
| i)  | <b>BRM255</b> : Weather Coat (I.S.I.)  | 0.125  | 10.185   | 1 Ltr   |
| ii) | <b>BRM252</b> : Wall cement primer (I.S.I.) Oil bound  | 0.084  | 6.84432  | 1 Ltr   |
| 12  | <b>Roofing (AR1132)</b><br>:.Supplying, feeting & fixing of G.C.I. Sheet (0.30mm thick) in roof drilling hole in wind ties - Supplying, fitting & fixing of G.C.I. Sheet (0.30mm thick) in roof drilling hole in wind ties including fixing of ridges valleys wind ties etc. including cost of fitting, Labour and material etc. complete as per direction of Engineer-in-Charge | -      | 9        | Sqm     |
| i)  | <b>BRM149</b> : G.C.I. Sheet 0.30mm thick  | 1      | 9        | 1 Sqm   |
| 13  | <b>Iron Work(AR1704)</b><br>:.Iron Doors and windows fixing - Supplying, fitting & fixing of Mild steel and put up for frames & shutters of Doors and windows fixing in position with cost, conveyance, taxes of all materials, labours and T & P required for the work etc. as per direction of Engineer-in-charge.   | -      | 2.588856 | Qntl    |
| i)  | <b>BRM341</b> : Steel  | 1      | 2.588856 | 1 Qntl. |
| 14  | <b>Flooring (AR0802ii)</b><br>:.2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG Hand broken chips - 2.5 cm thick A.S. flooring in C.C (1:2:4) with 12 mm size HG Hand broken chips including punning incl. cost, conveyance & royalty of materials as per direction of Engineer-in-charge.  | -      | 9        | Sqm     |
| i)  | <b>BRM340</b> : Cement   | 0.0858 | 0.7722   | 1 Qntl. |
| ii) | <b>BRM028</b> : Screened and washed sharp sand for mortar  | 0.012  | 0.108    | 1 Cum   |

|      |  |       |             |         |
|------|--|-------|-------------|---------|
| iii) | <b>BRM057</b> : Granite Stone broken chips 12mm. size (Minimum 65% by Wt. Passing through 13.2mm sieve & retained on 9.50mm sieve but whole should pass through 19mm sieve)(Hand broken)   | 0.023 | 0.207       | 1 Cum.  |
| 15   | <b>Iron Work(AR1703)</b><br>:.Iron work wrought and put up in trusses and record racks - Iron work wrought and put up in trusses and record racks including all cost of labour, material, machinery and T & P required for the work etc. as per direction of Engineer-in-Charge. | -     | <b>0.48</b> | Qntl    |
| i)   | <b>BRM341</b> : Steel  | 1     | 0.48        | 1 Qntl. |

| S/N                        | Material Name | Qty       | Unit   | Royalty Rate | Amount       |
|----------------------------|---------------|-----------|--------|--------------|--------------|
| 1                          | <b>BRM029</b> | 2.87      | 1 Cum  | 109.25       | 313.5475     |
| 2                          | <b>BRM028</b> | 7.966962  | 1 Cum  | 109.25       | 870.3905985  |
| 3                          | <b>BRM044</b> | 5.808     | 1 Cum. | 176.8        | 1026.8544    |
| 4                          | <b>BRM060</b> | 0.7895088 | 1 Cum. | 176.8        | 139.58515584 |
| 5                          | <b>BRM052</b> | 1.1842632 | 1 Cum. | 176.8        | 209.37773376 |
| 6                          | <b>BRM057</b> | 0.207     | 1 Cum. | 176.8        | 36.5976      |
| <b>Total: 2596.3529881</b> |               |           |        |              |              |

#### ADDITION COMPONENT

| SI.No.   | Item Name                        | Amount (in Rs.)     |
|--|----------------------------------|---------------------|
| 1  | Provision for Contingency @ 1%   | Rs. 1963.7641019972 |
| 2  | Display Citizen Board @ Rs. 1000 | Rs. 1000            |
| 3  | Any Other Lumpsum @ Rs. 659      | Rs. 659             |
| <b>Total Addition Component Amount (in Rs.): 3622.7641019972</b> |                                  |                     |

**Total Net Amount (in Rs.): 199999.17430172**