

BILLING DPR							
State	Odisha	District	Kendujhar	Block	Joda	Gram Panchayat	Bhuyanraida
Work Code	OD/361/3451/119439/385292/00057936 (CONSTRUCTION OF SANITARY COMPLEX TOILET AT CAMP HUTTING SCHOOL KOLHAROIDA)						
Project Category	Building						
Financial Year	2025-26	Execution Level	PS				
Executing Agency	Panchayat Samiti, Joda	Bill Status	Final Bill				
Proposal Date	31-05-2025	Date of Commencement	09-12-2025				
Date of Completion	15-12-2025	Scheme Name	SFC Devolution of Fund				
Scheme Component Name	5TH SFC DEVOLUTION GRANT TO PANCHAYAT SAMITI	Project Sub-Category	Elementary School				
Project Type	New Work	Name of Executant					

Administrative Approval Details

Approval No.	OD/361/3451/119439/385292/00057936/AS
--------------	---------------------------------------

Technical Sanction Details

Technical Sanction No.	OD/361/3451/119439/385292/00057936/TS
Fund Sanction No.	14036
Fund Sanction Amount (in Rs.)	200000

MATERIAL STATEMENT

Sl.No.	Activity Name/Material	Qty/unit (B=Analysis Basic Qty/Header Unit)	Quantity (Meaurement Qty)	Unit
1	Earth Work (AR0102aa) :.Earth work in hard soil or gravelly soil foundation & plinth within 50m. Initial lead and 1.5m initial lift - Earth work in hard soil or gravelly soil foundation & plinth within 50m. Initial lead and 1.5m initial lift including rough dressing and breaking clods to maximum 5cm to 7cm and laying in layers not exceeding 0.3m in depth and as per the direction of the Engineer-in-charge	-	9.8445	Cum
2	Earth Work (AR0115) :.Filling foundation and plinth with sand well watered and rammed - Filling foundation and plinth with sand well watered and rammed including cost, conveyance, royalty, taxes of all materials, labours and T & P required for the work etc. complete and as per direction of Engineer-in charge.	-	1.8779	Cum
i)	BRM029 : Sand for filling and road blinding	1	1.8779	1 Cum

3	Concrete (AR0303) :Cement concrete (1:3:6) with 4 cm. Crusher Broken hard granite metal - Cement concrete (1:3:6) with 4 cm. hard granite(Crusher Broken) metal including laying in layers not exceeding 300 mm in depth, ramming, compacting to proper thickness, watering and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&P required for the work etc. complete and as per direction of Engineer-in charge.	-	1.6569	Cum
i)	BRM340 : Cement	2.29	3.794301	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.48	0.795312	1 Cum
iii)	BRM044 : Granite Stone broken metal 40mm. size (Crusher broken)	0.96	1.590624	1 Cum.
4	Masonry Brick Work (AR0603b) :.Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in foundation and plinth - Brickwork with Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in foundation and plinth having crushing strength not less than 75.00 Kg/cm2 with dimensional tolerance ± 8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&P required for the work, etc. complete and as per direction of Engineer-in-charge.	-	7.14285	Cum
i)	BRM340 : Cement	0.672	4.7999952	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.28	1.999998	1 Cum
iii)	BRM005 : Fly ash bricks of 25 Cm. x 12 Cm. x 8 Cm. size having crushing strength not less than 75 Kg./Cm2 with dimensional tolerance ± 2 %	350	2499.9975	1000 Nos
5	R.C.C. Work (AR0404Ab) :.Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips - Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC Plinth band)	-	0.36975	Cum
i)	BRM340 : Cement	3.4733	1.284252675	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.45	0.1663875	1 Cum
iii)	BRM060 : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)	0.36	0.13311	1 Cum.
iv)	BRM052 : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)	0.54	0.199665	1 Cum.
v)	BRM104 : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)	0.01335	0.0049361625	1Cum.
vi)	BRM092 : Non-sal bullahs 75mm. mean dia of any length.	0.63	0.2329425	1Mtr.

6	R.C.C. Work (AR0404Ac) :.Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips - Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge. (RCC Beams, Column, Girder & Bressmer etc)	-	0.22125	Cum
i)	BRM340 : Cement	3.4733	0.768467625	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.45	0.0995625	1 Cum
iii)	BRM060 : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)	0.36	0.07965	1 Cum.
iv)	BRM052 : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)	0.54	0.119475	1 Cum.
v)	BRM084 : Sal bullahs 75mm. to 120mm. mean dia up to 5.5m. long.	4.4196	0.9778365	1Mtr
vi)	BRM104 : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)	0.041529	0.00918829125	1Cum.
7	R.C.C. Work (AR0404Ag) :.Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips - Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC Roof slab, landing, balcony, sun shade)	-	1.38985	Cum
i)	BRM340 : Cement	3.4733	4.827366005	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.45	0.6254325	1 Cum
iii)	BRM060 : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)	0.36	0.500346	1 Cum.
iv)	BRM052 : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)	0.54	0.750519	1 Cum.
v)	BRM084 : Sal bullahs 75mm. to 120mm. mean dia up to 5.5m. long.	6.2216	8.64709076	1Mtr
vi)	BRM104 : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)	0.0502172	0.06979437542	1Cum.

8	Masonry Brick Work (AR0603bi) :.Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure - Brickwork with Flyash Bricks of size (25cm x 12cm x 8cm) in cement mortar (1:6) in superstructure having crushing strength not less than 75.00 Kg/cm2 with dimensional tolerance ±8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&P required for the work, etc. complete and as per direction of Engineer-in-charge.	-	4.8465	Cum
i)	BRMMR0025 : SCAFFOLDING CHARGES FOR BRICK MASONRY WORK	1	4.8465	1 Cum
ii)	BRM340 : Cement	0.672	3.256848	1 Qntl.
iii)	BRM028 : Screened and washed sharp sand for mortar	0.28	1.35702	1 Cum
iv)	BRM005 : Fly ash bricks of 25 Cm. x 12 Cm. x 8 Cm. size having crushing strength not less than 75 Kg./Cm2 with dimensional tolerance ± 2 %	350	1696.275	1000 Nos
9	R.C.C. Work (AR0409) :.Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position - Supplying, fitting, and placing uncoated HYSD bar reinforcement including labor charges for cutting, bending, binding, and tying the grills and placing in position including cost of binding wire 18 to 20 gauge with cost of steel rod and as per drawing, design, and direction of Engineer-in-charge.	-	1.96	Qntl
i)	BRM162 : Binding Wire.	0.8	1.568	1 Kg.
ii)	BRM341 : Steel	1.05	2.058	1 Qntl.
10	Other Building Items. (AR1901B) :.Vitrified Tile 600mmx600mm Plain Ivory - Supplying, fitting & fixing Vitrified Tile 600mmx600mm Plain Ivory in floors of size 600mm x 600 mm of approved make conforming IS:13755 laid on 20 mm thick cement mortar(1:4)and filling joints with white cement of approved quality including cost of all materials, taxes, labour, T&P , etc. required for the work all complete as per direction of Engineer-in-charge(for new work only)	-	4.42	Sqm
i)	BRM174 : White Cement.	0.0076	0.033592	1Qntl
ii)	BRM340 : Cement	0.1074	0.474708	1 Qntl.
iii)	BRM028 : Screened and washed sharp sand for mortar	0.021	0.09282	1 Cum
iv)	BRM131 : Tiles up to Polished Vitrified floor tiles of premium grade having thickness 8 mm to 10mm confirming to IS 15622:2006 (Group-B la) of sizes Vitrified Tile 600mmx600mm Plain (Ivory)	1	4.42	1 Sqm.
11	Flooring (AR0817b) :.Fixing ceramic tiles (20cmx30cm / 20cmx20cm special plain/printed series ceramic wall tiles of premium grade having thickness 6.5mm to 6.7mm confirming to IS 13753) - Fixing ceramic tiles (20cmx30cm / 20cmx20cm special plain/printed series ceramic wall tiles of premium grade having thickness 6.5mm to 6.7mm confirming to IS 13753) in wall cladding on 12mm thick cement plaster (1:3) jointed with neat cement slurry mixed with pigments to match the shade of the ceramic tiles including rubbing and polishing, cost of precast tiles complete as per direction of Engineer-in-charge.	-	12.6	Sqm
i)	BRM129 : Tiles up to 20cmx30cm / 20cm x 20cm special plain /printed series ceramic wall tiles of premium grade having thickness 6.5mm to 6.7mm confirming to IS 13753	1	12.6	1 Sqm.

ii)	BRM340 : Cement	0.1375	1.7325	1 Qntl.
iii)	BRM028 : Screened and washed sharp sand for mortar	0.015	0.189	1 Cum
12	Iron Work(AR1704) :.Iron Doors and windows fixing - Supplying, fitting & fixing of Mild steel and put up for frames & shutters of Doors and windows fixing in position with cost, conveyance, taxes of all materials, labours and T & P required for the work etc. as per direction of Engineer-in-charge.	-	1.02375	Qntl
i)	BRM341 : Steel	1	1.02375	1 Qntl.
13	Plastering (AR1017) :.20mm thick cement Plaster in CM (1:4) over masonry work in inside. - 20mm thick cement Plaster in CM (1:4) over stone work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc comp.and as per direction of Engineer-in-charge.	-	10.4135	Sqm
i)	BRM340 : Cement	0.0744	0.7747644	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.021	0.2186835	1 Cum
14	Plastering (AR1004) :.12mm thick cement plaster (1:6) over Brick work in inside - 12mm thick cement plaster (1:6) over Brick work in inside including racking out joints finishing smooth with proper plumb and line curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc. comp.and as per direction of Engineer-in-charge.	-	38.9235	Sqm
i)	BRM340 : Cement	0.0358	1.3934613	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.015	0.5838525	1 Cum
15	Plastering (AR1014) :.16mm thick cement Plaster in CM (1:6) over brick work in inside. - 16mm thick cement Plaster in CM (1:6) over brick work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc comp.and as per direction of Engineer-in-charge.	-	23.6475	Sqm
i)	BRM340 : Cement	0.043	1.0168425	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.018	0.425655	1 Cum
16	Plastering (AR1027) :.6mm thick cement Plaster in CM (1:4) over R.C.C. surfaces including chipping (Inside) - 6mm thick cement Plaster in CM (1:4) over R.C.C. surfaces in inside including chipping with proper level and line, curing for the proper period with cost conveyance, royalty, taxes of all materials, labor, and T & P required for the work, etc comp. and as per the direction of the Engineer-in-charge.	-	11.074	Sqm
i)	BRM340 : Cement	0.0372	0.4119528	1 Qntl.
ii)	BRM028 : Screened and washed sharp sand for mortar	0.0075	0.083055	1 Cum
17	Painting(AR0919b) :.Finishing wall surface with One Coat with plastic emulsion paint of approved shades above one coat water bound Primer on old work (Inside) - Finishing wall surface with One Coat with plastic emulsion paint of approved shades above one coat waterbound Primer on old work to give an even shade including all costs of labor, Paint, Primer, Brushes and putty required for the work, etc. complete and as per direction of the Engineer-in-charge..(Inside)	-	34.7215	Sqm
i)	BRM140 : Plastic Emulsion paint	0.075	2.6041125	1 Litre

ii)	BRM253 : Wall cement primer (I.S.I.) Water bound	0.084	2.916606	1 Ltr
18	Painting(AR0918cb) :.Finishing wall two coats with weather coat with one coat waterbound Primer - Finishing wall two coats with weather coat with one coat waterbound Primer including all costs of labour, Paint, Primer, Brushes and putty required for the work etc. complete and as per direction of Engineer-in-charge.(Outside)	-	26.6835	Sqm
i)	BRM255 : Weather Coat (I.S.I.)	0.125	3.3354375	1 Ltr
ii)	BRM253 : Wall cement primer (I.S.I.) Water bound	0.090322580645161	2.4101225806452	1 Ltr
19	Painting(AR0903b) :.Painting two coats of enamel paint with a coat of red oxide primer over iron surface - Painting two coats of enamel paint with a coat of red oxide primer over iron surface including all costs of labour, Paint, Primer, brushes and putty required for the work etc. complete and as per direction of Engineer-in-charge.	-	6.58125	Sqm
i)	BRM137 : Red oxide Primer	0.054	0.3553875	1 Litre
ii)	BRM141 : Enamel paint	0.125	0.82265625	1 Litre

Sl.No.	Material Name	Qty	Unit	Rate	Amount
1	BRM029	1.8779	1 Cum	1652.91	3103.999689
2	BRM340	24.535459505	1 Qntl.	604.197	14824.251026542
3	BRM028	6.6367785	1 Cum	1662.91	11036.365335435
4	BRM044	1.590624	1 Cum.	2271.16	3612.56160384
5	BRM005	4196.2725	1000 Nos	6.4484	27059.243589
6	BRM060	0.713106	1 Cum.	2694.58	1921.52116548
7	BRM052	1.069659	1 Cum.	2610.91	2792.78337969
8	BRM104	0.08391882917	1Cum.	58668.206	4923.3671570244
9	BRM092	0.2329425	1Mtr.	324.226	75.526015005
10	BRM084	9.62492726	1Mtr	345.286	3323.3526338964
11	BRMMR0025	4.8465	1 Cum	33	159.9345
12	BRM162	1.568	1 Kg.	90.1	141.2768
13	BRM341	3.08175	1 Qntl.	6878.257	21197.06850975
14	BRM174	0.033592	1Qntl	2053.857	68.993164344
15	BRM131	4.42	1 Sqm.	663.9538891	2934.676189822
16	BRM129	12.6	1 Sqm.	418.0738891	5267.73100266
17	BRM140	2.6041125	1 Litre	243.36677	633.75444784162
18	BRM253	5.3267285806452	1 Ltr	159.39677	849.06333042152
19	BRM255	3.3354375	1 Ltr	195.15677	650.93320903687
20	BRM137	0.3553875	1 Litre	143.06677	50.844141723375
21	BRM141	0.82265625	1 Litre	205.70677	169.22596000781
Total:					104796.47285052