

ESTIMATION DPR							
<b>State</b>	Odisha	<b>District</b>	Ganjam	<b>Block</b>	Kukudakhandi	<b>Gram Panchayat</b>	Dakhinapur

<b>Work Code</b>	OD/354/3378/117862/412577/00064287 (COMPLETION OF INCOMPLETE AWC-I BUILDING AT DAKHINAPUR)
<b>Project Category</b>	Building

<b>Financial Year</b>	2025-26	<b>Execution Level</b>	PS
<b>Executing Agency</b>	Panchayat Samiti, Kukudakhandi	<b>Proposal Date</b>	07-07-2025
<b>Date of Commencement</b>	15-11-2025	<b>Date of Completion</b>	16-01-2026
<b>Scheme Name</b>	Asset Management Women and Child Development Department	<b>Scheme Component Name</b>	Self/Personal Deposit
<b>Project Sub-Category</b>	AWC	<b>Project Type</b>	New Work
<b>Name of Executant</b>	ASWIN SUBUDHI		

### Administrative Approval Details

<b>Approval No.</b>	OD/354/3378/117862/412577/00064287/AS
---------------------	---------------------------------------

### Technical Sanction Details

<b>Technical Sanction No.</b>	OD/354/3378/117862/412577/00064287/TS
<b>Fund Sanction No.</b>	8405
<b>Fund Sanction Amount (in Rs.)</b>	200000

### MATERIAL STATEMENT

Sl.No.	Activity Name/Material	Qty/unit (B=Analysis Basic Qty/Header Unit)	Quantity (Meaurement Qty)	Unit
1	<b>Earth Work (AR0102aa) :.Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift - Earth work in hard soil or gravelly soil foundation &amp; plinth within 50m. Initial lead and 1.5m initial lift including rough dressing and breaking clods to maximum 5cm to 7cm and laying in layers not exceeding 0.3m in depth and as per the direction of the Engineer-in-charge</b>	-	1.296	Cum

2	<b>Earth Work (AR0115)</b> :.Filling foundation and plinth with sand well watered and rammed - Filling foundation and plinth with sand well watered and rammed including cost, conveyance, royalty, taxes of all materials, labours and T & P required for the work etc. complete and as per direction of Engineer-in charge.	-	1.764	Cum
i)	<b>BRM029</b> : Sand for filling and road blinding	1	1.764	1 Cum
3	<b>Concrete (AR0303)</b> :.Cement concrete (1:3:6) with 4 cm. Crusher Broken hard granite metal - Cement concrete (1:3:6) with 4 cm. hard granite(Crusher Broken) metal including laying in layers not exceeding 300 mm in depth, ramming, compacting to proper thickness, watering and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&P required for the work etc. complete and as per direction of Engineer-in charge.	-	0.459	Cum
i)	<b>BRM340</b> : Cement	2.29	1.05111	1 Qntl.
ii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.48	0.22032	1 Cum
iii)	<b>BRM044</b> : Granite Stone broken metal 40mm. size (Crusher broken)	0.96	0.44064	1 Cum.
4	<b>Earth Work (AR0114)</b> :.Filling of foundation with escalated earth - Filling in foundation and plinth with excavated materials in ordinary soil including watering and ramming as directed by the Engineer-in-charge.	-	0.496125	Cum

5	<p><b>Dismantling (AR1618)</b>  <b>:.Dismantling and removing doors, windows and ventilators -</b>  Dismantling and removing doors, windows and ventilators including removal of frame, hinges, fastening and stacking the same for reuse and removing the debris within 50m and as per direction of Engineer-in-Charge.</p>	-	1.104	Sqm
6	<p><b>Dismantling (AR1603)</b>  <b>:.Dismantling brick or stone masonry under 3m. -</b> Dismantling brick or stone masonry in lime or cement mortar under 3m. height including stacking the useful materials for reuse and removing the debris within 50m. Lead and as per direction of Engineer-in-Charge.</p>	-	0.44436	Cum
7	<p><b>Flooring (AR0817b)</b>  <b>:.Fixing ceramic tiles (20cmx30cm / 20cmx20cm special plain/printed series ceramic wall tiles of premium grade having thickness 6.5mm to 6.7mm confirming to IS 13753) -</b> Fixing ceramic tiles (20cmx30cm / 20cmx20cm special plain/printed series ceramic wall tiles of premium grade having thickness 6.5mm to 6.7mm confirming to IS 13753) in wall cladding on 12mm thick cement plaster (1:3) jointed with neat cement slurry mixed with pigments to match the shade of the ceramic tiles including rubbing and polishing, cost of precast tiles complete as per direction of Engineer-in-charge.</p>	-	6.075	Sqm

i)	<b>BRM129</b> : Tiles up to 20cmx30cm / 20cm x 20cm special plain /printed series ceramic wall tiles of premium grade having thickness 6.5mm to 6.7mm confirming to IS 13753	1	6.075	1 Sqm.
ii)	<b>BRM340</b> : Cement	0.1375	0.8353125	1 Qntl.
iii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.015	0.091125	1 Cum
8	<b>Flooring (AR0817aa)</b> :.Fixing Vitrified tiles of premium grade having thickness 8mm to 10mm confirming to IS 13756 of size 600mmx600mm plain (Ivory) in dados skirting and risers of steps on 12mm thick cement plaster (1:3) - Fixing Vitrified tiles of premium grade having thickness 8mm to 10mm confirming to IS 13756 of size 600mmx600mm plain (Ivory) in dados skirting and risers of steps on 12mm thick cement plaster (1:3) jointed with neat cement slurry mixed with pigments to match the shade of the Vitrified tiles including rubbing and polishing complete including cost of precast tiles.	-	5.562	Sqm
i)	<b>BRM131</b> : Tiles up to Polished Vitrified floor tiles of premium grade having thickness 8 mm to 10mm confirming to IS 15622:2006 (Group-B la) of sizes Vitrified Tile 600mmx600mm Plain (Ivory)	1	5.562	1 Sqm.
ii)	<b>BRMMR0027</b> : Wax Polish	1	5.562	1 Sqm
iii)	<b>BRM340</b> : Cement	0.1375	0.764775	1 Qntl.
iv)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.015	0.08343	1 Cum

9	<p><b>Flooring (AR0816)</b>  <b>:.Fixing ceramic Tiles (30cmx30cm / 40cmx40cm special plain/printed series ceramic floor tiles of premium grade having thickness 7mm to 8mm confirming to IS 13755) in floor -</b> Fixing ceramic Tiles (30cmx30cm / 40cmx40cm special plain/printed series ceramic floor tiles of premium grade having thickness 7mm to 8mm confirming to IS 13755) in floor , treads or steps and landing on a 25mm thick bed of cement mortar 1:1 (1cement: 1sand) jointed with neat cement slurry mixed with pigment to match the shades of the ceramic tiles including rubbing and polishing, cost of precast tiles complete as per direction of Engineer-in-charge.</p>	-	1.44	Sqm
i)	<b>BRMMR0027</b> : Wax Polish	1	1.44	1 Sqm
ii)	<b>BRM130</b> : Tiles up to 30cm x 30cm / 40cm x 40cm special plain / printed series ceramic floor tiles of premium grade having thickness 7mm to 8mm confirming to IS 13755	1	1.44	1 Sqm.
iii)	<b>BRM340</b> : Cement	0.2737	0.394128	1 Qntl.
iv)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.013	0.01872	1 Cum

10	<b>R.C.C. Work (AR0404Ab)</b> <b>:.Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b> Reinforced cement concrete work of M-20 grade with 20mm & down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC Plinth band)	-	<b>0.214774</b>	Cum
i)	<b>BRM340</b> : Cement	3.4733	0.7459745342	1 Qntl.
ii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.45	0.0966483	1 Cum
iii)	<b>BRM060</b> : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)	0.36	0.07731864	1 Cum.
iv)	<b>BRM052</b> : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)	0.54	0.11597796	1 Cum.
v)	<b>BRM104</b> : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)	0.01335	0.0028672329	1Cum.
vi)	<b>BRM092</b> : Non-sal bullahs 75mm. mean dia of any length.	0.63	0.13530762	1Mtr.

11	<p><b>R.C.C. Work (AR0404Ag)</b>  <b>:.Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips -</b>  Reinforced cement concrete work of M-20 grade with 20mm &amp; down grade size black hard crusher broken granite chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty,taxes of all materials, labour and T&amp;P required for the work etc. (including centring and shuttering) complete and as per direction of Engineer-in charge (RCC Roof slab, landing, balcony, sun shade)</p>	-	<b>0.493725</b>	Cum
i)	<b>BRM340</b> : Cement	3.4733	1.7148550425	1 Qntl.
ii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.45	0.22217625	1 Cum
iii)	<b>BRM060</b> : Granite Stone broken chips 10mm. size (Minimum 65% by Wt. Passing through 9.5mm sieve & retained on 6.3mm sieve but whole should pass through 13.2mm sieve) (Crusher broken)	0.36	0.177741	1 Cum.
iv)	<b>BRM052</b> : Granite Stone broken chips 20mm. size (Minimum 65% by Wt. Passing through 19mm sieve & retained on 13.2mm sieve but whole should pass through 26.5mm sieve) (Crusher broken)	0.54	0.2666115	1 Cum.
v)	<b>BRM084</b> : Sal bullahs 75mm. to 120mm. mean dia up to 5.5m. long.	6.2216	3.07175946	1Mtr
vi)	<b>BRM104</b> : Non Sal wood scantling & plants(Tentera, Kasi, Gamhari, Kuruma)	0.0502172	0.02479348707	1Cum.

12	<b>Plastering (AR1004)</b> <b>::12mm thick cement plaster (1:6) over Brick work in inside</b> - 12mm thick cement plaster (1:6) over Brick work in inside including racking out joints finishing smooth with proper plumb and line curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc. comp.and as per direction of Engineer-in-charge.	-	<b>9.3885</b>	Sqm
i)	<b>BRM340</b> : Cement	0.0358	0.3361083	1 Qntl.
ii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.015	0.1408275	1 Cum
13	<b>Plastering (AR1014)</b> <b>::16mm thick cement Plaster in CM (1:6) over brick work in inside.</b> - 16mm thick cement Plaster in CM (1:6) over brick work in inside including racking out joints finishing smooth with proper plumb and line, curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T & P required for the work etc comp. and as per direction of Engineer-in-charge.	-	<b>15.504</b>	Sqm
i)	<b>BRM340</b> : Cement	0.043	0.666672	1 Qntl.
ii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.018	0.279072	1 Cum

14	<p><b>Masonry Brick Work (AR0603c) :.Flyash Bricks of size (23cm x 11cm x 8cm) in cement mortar (1:6) in foundation and plinth</b>  - Brickwork with Flyash Bricks of size (23cm x 11cm x 8cm) in cement mortar (1:6) in foundation and plinth having crushing strength not less than 75.00 Kg/cm<sup>2</sup> with dimensional tolerance ±8 percent immersing the bricks in water not less than six hours with cost conveyance, royalty, taxes of all materials, labor, and T&amp;P required for the work, etc. complete and as per direction of Engineer-in-charge.</p>	-	3.010066	Cum
i)	<p><b>BRM006</b> : Fly ash bricks of 23 Cm. x 11 Cm. x 8 Cm. size having crushing strength not less than 75 Kg./Cm<sup>2</sup> with dimensional tolerance ± 2 %</p>	400	1204.0264	1000 Nos
ii)	<p><b>BRM340</b> : Cement</p>	0.672	2.022764352	1 Qntl.
iii)	<p><b>BRM028</b> : Screened and washed sharp sand for mortar</p>	0.28	0.84281848	1 Cum
15	<p><b>Painting(AR0920) :.Finishing wall two coats with plastic emulsion paint of approved shades on new work (Inside) -</b>  Finishing wall two coats with plastic emulsion paint of approved shades on new work to give an even shade including all costs of labor, Paint and Brushes required for the work, etc. complete and as per direction of the Engineer-in-charge.(Inside)</p>	-	144.2534	Sqm
i)	<p><b>BRM140</b> : Plastic Emulsion paint</p>	0.125	18.031675	1 Litre

16	<b>Painting(AR0903i)</b> :.Painting two coats of enamel paint in outer surface paint (outer surface) - Painting two coats of enamel paint in outer surface paint including all costs of labour, Paint and brushes required for the work etc. complete and as per direction of Engineer-in-charge.(Outside)	-	24.288	Sqm
i)	<b>BRM141</b> : Enamel paint	0.125	3.036	1 Litre
17	<b>Other Building Items. (AR1909)</b> :.Al. door with OEL anodized Al. door section of 9202 as vertical member - Providing fitting, fixing of Al. door with OEL anodized Al. door section of 9202 as vertical member, 9201 as top member and 9200 as bottom and middle member and 12mm thick pre-laminated board fixed on door frame by means of tapered clip No. 4660 and the frame to be completed by means of jointing angle No.1855 including all cost of labour,T&P , hire charges of drilling machine, labour charges etc. complete. and as per direction of Engineer in Charge	-	1.188	Sqm
i)	<b>BRM281</b> : Prelaminated particle board (standard type) (I.S.I.) 12mm	1.1018518518519	1.309	Sqm
ii)	<b>BRMMR0008</b> : Hire charges of drills machine	0.694444444444444	0.825	Day
iii)	<b>BRMMR0018</b> : 6-Level mortice lock	0.46296296296296	0.55	Each
iv)	<b>BRMMR0017</b> : Handle	0.92592592592593	1.1	Each
v)	<b>BRMMR0016</b> : Door Stopper	0.46296296296296	0.55	Each
vi)	<b>BRMMR0011</b> : U rubber beading	8.4675925925926	10.0595	Mtr
vii)	<b>BRMMR0015</b> : 4 Anodised Al. Hinges	1.8518518518519	2.2	Each

viii)	<b>BRM304</b> : Aluminium extruded section	11.821805555556	14.044305	kg
18	<b>Concrete (AR0307) :Cement concrete (1:2:4)with 12mm size hard broken granite chips per 1cum -</b> Cement concrete work with (1:2:4) using 12mm size hard granite(crusher broken) chips including hoisting and laying in position compacting to specified design section and curing for proper period with cost conveyance, royalty, taxes of all materials, labour and T&P required for the work etc. complete as per specificaion and direction of Engineer-in charge.	-	<b>1.3078</b>	Cum
i)	<b>BRM340</b> : Cement	3.23	4.224194	1 Qntl.
ii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.45	0.58851	1 Cum
iii)	<b>BRM056</b> : Granite Stone broken chips 12mm. size (Minimum 65% by Wt. Passing through 13.2mm sieve & retained on 9.50mm sieve but whole should pass through 19mm sieve) (Crusher broken)	0.9	1.17702	1 Cum.
19	<b>Other Building Items. (AR1901B) :.Vitrified Tile 600mmx600mm Plain Ivory -</b> Supplying, fitting & fixing Vitrified Tile 600mmx600mm Plain Ivory in floors of size 600mm x 600 mm of approved make conforming IS:13755 laid on 20 mm thick cement mortar(1:4)and filling joints with white cement of approved quality including cost of all materials, taxes, labour, T&P , etc. required for the work all complete as per direction of Engineer-in-charge(for new work only)	-	<b>52.7818</b>	Sqm
i)	<b>BRM174</b> : White Cement.	0.0076	0.40114168	1Qntl

ii)	<b>BRM340</b> : Cement	0.1074	5.66876532	1 Qntl.
iii)	<b>BRM028</b> : Screened and washed sharp sand for mortar	0.021	1.1084178	1 Cum
iv)	<b>BRM131</b> : Tiles up to Polished Vitrified floor tiles of premium grade having thickness 8 mm to 10mm confirming to IS 15622:2006 (Group-B la) of sizes Vitrified Tile 600mmx600mm Plain (Ivory)	1	52.7818	1 Sqm.
20	<b>miscellaneous(ARM287) :.Supplying and fixing of 80mm thick cement concrete interlocking paver block of M-40 grade of approved make, design, colour and size made by Block making machine with proper compaction laid in required pattern etc. complete in all respect conforming to IRC - Supplying and fixing of 80mm thick cement concrete interlocking paver block of M-40 grade of approved make, design, colour and size made by Block making machine with proper compaction laid in required pattern etc. complete in all respect conforming to IRC SP-63:2018. (New miscellaneous items) and as directed by Engineer-in-Charge.</b>	-	<b>22.8</b>	Sqm
i)	<b>BRM029</b> : Sand for filling and road blinding	0.03	0.684	1 Cum
ii)	<b>BRMM287</b> : Supplying and fixing of 80mm thick cement concrete interlocking paver block of M-40 grade of approved make, design, colour and size made by Block making machine with proper compaction laid in required pattern etc. complete in all respect conforming to IRC SP-63:2018. (New miscellaneous items)	1	22.8	1 Sqm

21	<p><b>miscellaneous(ARM29 5) :.Supplying, fitting and fixing of 5.5mm thick hexagoanal Aluminum jally in windows as single groove, double groove and tapered clip as horizontal and vertical members for fixing of aluminum jally and jointing angle conforming to standard Aluminium sections -</b> Supplying, fitting and fixing of 5.5mm thick hexagoanal Aluminum jally in windows as single groove, double groove and tapered clip as horizontal and vertical members for fixing of aluminum jally and jointing angle conforming to standard Aluminium sections etc. complete. (New miscellaneous items) and as directed by Engineer-in-Charge.</p>	-	2.2448	Sqm
i)	<p><b>BRMM295 :</b> Supplying, fitting and fixing of 5.5mm thick hexagoanal Aluminum jally in windows as single groove, double groove and tapered clip as horizontal and vertical members for fixing of aluminum jally and jointing angle conforming to standard Aluminium sections etc. complete. (New miscellaneous items)</p>	1	2.2448	1 Sqm

22	<b>Painting(AR0918c)</b> :.Finishing wall with two coat water proofing cement paint including one coat cement wash on the outer surface of approved shade on new work (Outside) - Finishing wall with two coat water proofing cement paint including one coat cement wash on the outer surface of approved shade on new work to give an even shade including all costs of labour, Paint, Brushes, and putty required for the work, etc. complete and as per direction of Engineer-in-charge. (Outside)	-	104.72	Sqm
i)	<b>BRM143</b> : Cement paint	0.25	26.18	1 Kg.
ii)	<b>BRM340</b> : Cement	0.010763440860215	1.1271475268817	1 Qntl.

Sl.No.	Material Name	Qty	Unit	Rate	Amount
1	<b>BRM029</b>	2.448	1 Cum	534.17	1307.64816
2	<b>BRM340</b>	19.551806575582	1 Qntl.	598.962	11710.789170124
3	<b>BRM028</b>	3.69206533	1 Cum	537.54	1984.6327974882
4	<b>BRM044</b>	0.44064	1 Cum.	1336.36	588.8536704
5	<b>BRM129</b>	6.075	1 Sqm.	416.4375001	2529.8578131075
6	<b>BRM131</b>	58.3438	1 Sqm.	662.3175001	38642.119762334
7	<b>BRMMR0027</b>	7.002	1 Sqm	8.5	59.517
8	<b>BRM130</b>	1.44	1 Sqm.	461.3175001	664.297200144
9	<b>BRM060</b>	0.25505964	1 Cum.	1748.88	446.0687032032
10	<b>BRM052</b>	0.38258946	1 Cum.	1723.4	659.354675364
11	<b>BRM104</b>	0.02766071997	1Cum.	58620.646	1621.4892734665
12	<b>BRM092</b>	0.13530762	1Mtr.	276.666	37.43501799492
13	<b>BRM084</b>	3.07175946	1Mtr	297.726	914.54265698796
14	<b>BRM006</b>	1204.0264	1000 Nos	5.36398	6458.373529072
15	<b>BRM140</b>	18.031675	1 Litre	249.64732	4501.559338861
16	<b>BRM141</b>	3.036	1 Litre	205.64732	624.34526352
17	<b>BRM281</b>	1.309	Sqm	710.82	930.46338
18	<b>BRMMR0008</b>	0.825	Day	100	82.5
19	<b>BRMMR0018</b>	0.55	Each	600	330

20	<b>BRMMR0017</b>	1.1	Each	62.5	68.75
21	<b>BRMMR0016</b>	0.55	Each	25	13.75
22	<b>BRMMR0011</b>	10.0595	Mtr	15	150.8925
23	<b>BRMMR0015</b>	2.2	Each	39	85.8
24	<b>BRM304</b>	14.044305	kg	297.97	4184.78156085
25	<b>BRM056</b>	1.17702	1 Cum.	1737.73	2045.3429646
26	<b>BRM174</b>	0.40114168	1Qntl	2047.912	821.50286017216
27	<b>BRMM287</b>	22.8	1 Sqm	608.4	13871.52
28	<b>BRMM295</b>	2.2448	1 Sqm	1841	4132.6768
29	<b>BRM143</b>	26.18	1 Kg.	48.13732	1260.2350376
				<b>Total: 100729.09913529</b>	